

# Power Tank Instructions

## Power Tank 2 Door Sports Bar Mount - BKT-2220-D & BKT-2220-P


Thank you for purchasing a Power Tank 2 Door Sports Bar Mount! This install requires only basic hand tools. Install should take about 15 minutes. Please read all instructions first, before beginning the install. Note: There is a DRIVER side and a PASSENGER side version of this bracket. For the purposes of these instructions, we are mounting to the DRIVER side. This bracket fits 5 lb or 10 lb Power Tanks.

### What's included:

- (H1) 5x 3/8" x 1/2" button head bolt
- (H2) 5x 3/8" flanged nut
- (H3) 2x M8 button head bolt
- (H4) 2x M8 washer
- (H5) 2x White Spacer
- (P1) 1x Sports Bar Plate

### You will need:

- 9/16" wrench
- 7/32" allen wrench
- 5mm allen wrench
- Medium strength Loctite or threadlocker (optional)
- Power Tank Super Bracket (sold separately)



### Step 1: Bracket assembly

- A. Attach your Power Tank Super Bracket to the P1 Sports Bar Plate using (5) H1 3/8" bolts and (5) H2 3/8" nuts starting with the two in the center. The button head bolts should be facing away from the Power Tank.
- B. Mount the Super Bracket so the latch is on the same side as the PT decal on the P1 Sports Bar Plate.
- C. Remove the lower rubber trim piece from the Super Bracket *if mounting a 10 lb Power Tank*.



### Step 2: Attaching to sports bar

- A. Remove the plastic trim piece on the outside of the Jeep Sports Bar near the window of the desired mounting side. This reveals two threaded holes normally used to install the soft top. (your Jeep may not have the trim piece)
- B. Attach the bracket assembly to the Jeep Sports Bar using the (2) H3 M8 bolts and (2) H4 M8 washers in the two threaded holes from step 2A using 5mm allen wrench. If using Loctite, apply to H3 M8 bolts. Place the H5 White Spacers between the bracket assembly and Jeep Sports Bar.



### Step 3: Mounting Power Tank

- A. If you are mounting a 5 lb Power Tank, simply insert it into the Super Bracket and adjust the latch so it is snug but not too tight and then tighten the lock nut on the latch.
- B. If you are mounting a 10 lb Power Tank, insert it into the Super Bracket so the tank boot lip sits above the lower cradle of the Super Bracket which will help to support the weight. Adjust the latch so it is snug but not too tight and then tighten the lock nut on the latch. It is tight but will fit. You may have to rotate the tank.



PT05 - 5lb

PT10 - 10lb